ADDENDUM 2 FOR RFP# 2018-RFP-01 LIDAR and Aerial Image Acquisition for the Okanagan Valley Watershed



ADDENDUM #2

REQUEST FOR PROPOSALS

FOR

LIDAR AND AERIAL IMAGE ACQUISITION FOR THE OKANAGAN VALLEY WATERSHED

ADDENDUM 2 FOR RFP #: 2018-RFP-01 ISSUED ON: February 10th, 2018 RFP CLOSING DATE AND TIME: February 22nd, 2018 at 3:00pm Local Time

Page 1 of 2

ADDENDUM 2 FOR RFP# 2018-RFP-01

LIDAR and Aerial Image Acquisition for the Okanagan Valley Watershed

Additional Information for Proponents

Question: What is the minimum width we need to follow for river classification?

Answer: A: LiDAR pulses must be collected up to and including the physical boundary between land and water. The requirements for line work of rivers is to determine the shoreline as break line (SHAPE FILE FORMAT). This includes islands as well.

Question: Please confirm that we need to collect the following as breaklines.

- 1. Road edges
- 2. Ditches
- 3. Creeks
- 4. Terrain breaklines.

Answer: Affirmative (Confirmed)

Question: Page 6 **LiDAR Swath Overlap**: Please clarify that the specification for overlap is less than or equal to 30% and not greater than or equal to 30%. In other words can we plan on collecting greater than or equal to 50% overlap to achieve the density. Based on the way the specification is written, it does not appear so.

Answer: A minimum of 30% of flight line overlap